

Wireless Neural Recording

Wireless neural headstage systems for small animal research

Features & Benefits

- Monitor neural activity of freely moving rodents
- Record extracellular action potentials or field potentials
- Unparalleled sampling rates for high resolution signal acquisition
- Transmitters with convenient rechargeable battery
- Lightweight Headstage Receiver for easy portability
- Powerful data acquisition and analysis with PowerLab and LabChart Pro software
- Specialized software modules for advanced spike and waveform analysis.




The complete TBSI Wireless Neural Recording Systems feature the PowerLab data acquisition unit, industry-leading TBSI Headstage Transmitter & Headstage Receiver, as well as the powerful & flexible LabChart software.

ADInstruments and Triangle BioSystems Inc. (TBSI) give researchers a way to fast track their behavioral-electrophysiological studies with industry-leading systems for wireless acquisition of neural data. The systems are ideal for rodent studies that require high degrees of movement freedom as well as accurate and precise multichannel spike data.

TBSI provide small, lightweight headstages with 3.5 (5 channel) and 5.5 (15 channel) hour battery life, high sampling rates and a wireless transmission range of up to 4 meters. In combination with a PowerLab unit, and LabChart Pro software, researchers can acquire and analyze action potential signals (spikes) from individual neurons, as well as local and low frequency field potentials from freely moving small animals.

Flexible and easy to use systems:

- Record extracellular action potentials from individual neurons
- Record local and low frequency field potentials
- Suited to use in small animals such as rats and mice (4 m transmitter/receiver range)
- Ideal for studies including learning & memory, emotion & pathophysiology
- Test two subjects simultaneously with dual recording systems (i.e. social interaction test)
- Automatically detect & analyze multiple waveforms
- Discriminate & analyze extracellular neural spike activity
- Connect subject behavior with neural activity using the Video Capture Module
- Wireless Receiver Sets for researchers already using a PowerLab system with LabChart.



The Spike Histogram Module (above) is ideal for analyzing extracellular action potentials.

■ Data Acquisition and Analysis

Wireless Neural Recording Systems

These premier Wireless Neural Recording Systems are convenient to use, with the only wires running between the headstage Receiver and PowerLab data acquisition unit. With a wireless transmission range up to 4 m, the systems are ideal for rodent models.

Choose from a system with 5 or 15 channels, that includes a Wireless Neural Headstage and Receiver, 35 series PowerLab unit, LabChart Pro software with specialized analysis modules, plus interface and testing cables. Researchers already using PowerLab can extend the capability of their current system with a **TBSI Wireless Neural Headstage Receiver Set** (details below). All system hardware and software can be purchased individually.

Neural Headstage

- Compact and powerful with neural preamplifier circuitry
- Rechargeable battery
- Battery life:
15 Channel = 5.5 hrs
5 Channel = 3.5 hrs.



TBSI 5 Ch Wireless Neural Headstage Transmitter


Neural Receiver

- Small, lightweight and portable
- Supplied with: RF signal receiver/baseband demodulator & power supply.



TBSI 15 Ch Wireless Neural Headstage Receiver

Ordering Information

PL3508B82/F* 5 Channel Wireless Neural Recording System	PL3516B83/F* 15 Channel Wireless Neural Recording System
1 x PL3508/P PowerLab 8/35 with LabChart (Win & Mac) includes LabChart Pro software	1 x PL3516/P PowerLab 16/35 with LabChart (Win & Mac) includes LabChart Pro software
1 x TB5469/F TBSI 5 Ch Wireless Neural Headstage Receiver Set Includes 1 x each: TB5663/F TBSI 5 Channel Wireless Neural Receiver TB5653/F TBSI 5 Channel Wireless Neural Headstage** Power supply Accessories.	1 x TB5470/F TBSI 15 Channel Wireless Neural Headstage Receiver Set Includes 1 x each: TB5664/F TBSI 15 Channel Wireless Neural Receiver TB5656/F TBSI 15 Channel Wireless Neural Headstage** Power supply Accessories.
1 x MLAC55 TBSI Receiver to PowerLab Interface Cable (5 Ch)	1 x MLAC56 TBSI Receiver to PowerLab Interface Cable (15 Ch)
1 x MLAC51 TBSI 5 Ch Headstage Testing Cable	1 x MLAC52 TBSI 15 Ch Headstage Testing Cable
TB5469/F* TBSI 5 Channel Wireless Neural Headstage Receiver Set	*Ordering Notes: When ordering a complete system or headstage receiver set, please specify frequency (F) = 3 for 3GHz (standard) or 3.4 for 3.4GHz (alternate). **Headstage options: The wireless headstage is supplied standard as dipped. A covered option is available and must be specified at the time of purchase. The TBSI Headstage LED Option adds two LEDs to the headstage for video tracking (reduces battery life by 30%). The LEDs are placed superior to the headstage in an upward facing position and will operate in tandem with the headstage. Headstage LEDs and external batteries are available separately and must be specified at the time of headstage purchase.
1 x TB5663/F TBSI 5 Channel Wireless Neural Receiver	 Share your data with colleagues. Free LabChart Reader – download to view and analyze LabChart data.
1 x TB5653/F TBSI 5 Channel Wireless Neural Headstage**	
1 x Power supply and accessories	
TB5470/F* TBSI 15 Channel Wireless Neural Headstage Receiver Set	
1 x TB5664/F TBSI 15 Channel Wireless Neural Receiver	
1 x TB5656/F TBSI 15 Channel Wireless Neural Headstage**	
1 x Power supply and accessories	

PowerLab, MacLab, LabChart, LabTutor and LabAuthor are registered trademarks and Chart and Scope are trademarks of ADInstruments Pty Ltd. All other trademarks are the property of their respective owners. TBSI12/11

PowerLab systems and signal conditioners meet the European EMC directive. ADInstruments signal conditioners for human use are approved to the IEC60601-1 patient safety standard and meet the CSA C22.2 No. 601.1-M90 and UL Std No. 2601-1 safety of medical electrical equipment standards.



ADINSTRUMENTS.com

North America

Tel: +1 888 965 6040
Fax: +1 719 576 39713
info.na@adstruments.com

United Kingdom

Tel: +44 1865 332 050
Fax: +44 1865 332 051
info.uk@adstruments.com

Germany

Tel: +49 6226 970105
Fax: +49 6226 970106
info.de@adstruments.com

North Asia

Tel: +86 21 5830 5639
Fax: +86 21 5830 5640
info.cn@adstruments.com

South East Asia

Tel: +60 3 8024 5296
Fax: +60 3 8023 6307
info.sea@adstruments.com

Japan

Tel: +81 52 932 6462
Fax: +81 52 932 6755
info.jp@adstruments.com

South America

Tel: +56 2 356 6749
Fax: +56 2 356 6786
info.cl@adstruments.com

Brazil

Tel: +55 11 3266 2393
Fax: +55 11 3266 2392
info.br@adstruments.com

South Asia

IN Tel: +91 11 4306 5615
PK Tel: +92 21 3489 2518
info.in@adstruments.com

Australia

Tel: +61 2 8818 3400
Fax: +61 2 8818 3499
info.au@adstruments.com

New Zealand

Tel: +64 3 477 4646
Fax: +64 3 477 4346
info.nz@adstruments.com

International

Tel: +61 2 8818 3400
Fax: +61 2 8818 3499
info.au@adstruments.com

ISO 9001:2008 Certified Quality Management System

